

MissXss API AI Reference

This document is generated so AI tools can understand MissXss API endpoints, parameters, scope requirements, and request/response examples.

Base URL

<https://api.missxss.com.tr>

Authentication

Bearer

Endpoints

62

Quick Start

- Use Authorization: Bearer YOUR_API_KEY on every request.
- Send POST requests to <https://api.missxss.com.tr/v1/{scope}>.
- Use Content-Type: application/json and include only the parameters listed for the endpoint.

Chat & Messaging - 3 endpoints

POST

Send Message (As Broadcaster)

scope: send-message
limit: 90/min

<https://api.missxss.com.tr/v1/send-message>

Sends a chat message as the broadcaster account. The message appears under your own name.

Parameters

Name	Type	Req	Description
<code>message</code>	<code>string</code>	yes	Message text to send (1-500 characters)
<code>platform</code>	<code>string</code>	no	Target platform: Kick or Twitch (default: Kick)

Example Request Body

```
{"message": "Hello Chat!"}
```

Example Success Response

```
{"success": true, "message_id": "abc123"}
```

POST

Send Message (As Bot)

scope: send-bot-message
limit: 90/min

<https://api.missxss.com.tr/v1/send-bot-message>

Sends a chat message via the MissXss bot account. The message appears under the bot name.

Parameters

Name	Type	Req	Description
------	------	-----	-------------

message	string	yes	Message text to send (1-500 characters)
platform	string	no	Target platform: Kick or Twitch (default: Kick)

Example Request Body

```
{"message": "This is a bot message!"}
```

Example Success Response

```
{"success": true, "message_id": "def456"}
```

POST

Send TTS Message

scope: tts
limit: 20/min

<https://api.missxss.com.tr/v1/tts>

Reads a text-to-speech message on stream. The overlay must be connected. A per-minute rate limit applies.

Parameters

Name	Type	Req	Description
text	string	yes	Text to speak (1-500 characters)
username	string	no	Display username shown on screen (default: "API")

Example Request Body

```
{"text": "Hello Stream!", "username": "Bot"}
```

Example Success Response

```
{"success": true, "ttsId": "alb2c3d4..."}
```

Stream Controls - 6 endpoints

POST

Create Clip

scope: clip
limit: 20/min

<https://api.missxss.com.tr/v1/clip>

Creates a clip from the current live stream. Works via extension connection on Kick and API on Twitch. Stream must be live.

Parameters

Name	Type	Req	Description
title	string	no	Clip title (default: "Clip - MissXss API")
duration	integer	no	Clip duration (5-180 seconds, default: 30)

Example Request Body

```
{"title": "Epic moment!", "duration": 45}
```

Example Success Response

```
{"success": true}
```

POST

Change Game / Category

scope: game
limit: 20/min

<https://api.missxss.com.tr/v1/game>

Changes the stream category. Both Kick and Twitch are updated simultaneously. You can send a game name or Kick category ID; if both are sent, ID takes priority.

Parameters

Name	Type	Req	Description
game	string	no	Game/category name (e.g. "Valorant"). Required if kick_category_id is not sent.
kick_category_id	integer	no	Kick category ID. Sending the ID directly is faster if known.

Example Request Body

```
{"game": "Valorant"}
```

Example Success Response

```
{"success": true, "game": "VALORANT"}
```

POST

Smart Game / Category Search

scope: search-games
limit: 40/min

<https://api.missxss.com.tr/v1/search-games>

Performs a smart search in the game database. Exact name match, slug match, starts-with match, word containment and spelling similarity are scored together; closest games are returned based on similarity ratio.

Parameters

Name	Type	Req	Description
query	string	yes	Game/category name to search (2-100 chars). game or search is also accepted.
limit	integer	no	Maximum row count to return (1-50, default: 10)
min_similarity	number	no	Minimum similarity score (0-100, default: 25)

Example Request Body

```
{"query": "banana", "limit": 10}
```

Example Success Response

```
{"success": true, "query": "banana", "total": 3, "best_match": {"kick_category_id": 123, "name": "Banana", "slug": "banana", "score": 100, "match_type": "exact_name"}, "games": [{"kick_category_id": 123, "name": "Banana", "slug": "banana", "score": 100, "match_type": "exact_name"}]}
```

POST

Change Stream Title

<https://api.missxss.com.tr/v1/title>

Changes the stream title. Both Kick and Twitch are updated simultaneously.

scope: title
limit: 20/min

Parameters

Name	Type	Req	Description
title	string	yes	New stream title (1-140 characters)

Example Request Body

```
{"title":"New stream title!"}
```

Example Success Response

```
{"success":true}
```

POST

Get Stream Meta

<https://api.missxss.com.tr/v1/get-stream-meta>

Returns stream metadata via POST method, including viewer_count and followers_count.

scope: get-stream-meta
limit: 120/min

Parameters

Name	Type	Req	Description
platform	string	no	Kick or Twitch (default: Kick)

Example Request Body

```
{}
```

Example Success Response

```
{"success":true,"platform":"Kick","channel":"kanaladi","title":"Live Stream","category":"Just Chatting","category_id":"123","viewer_count":245,"followers_count":19234,"is_live_any":1,"is_live_kick":1,"is_live_twitch":0,"kick_category_id":"2026-04-18"}
```

POST

Set Stream Meta

<https://api.missxss.com.tr/v1/set-stream-meta>

Updates title and/or game metadata in one request. At least one of title, game or kick_category_id must be provided.

scope: set-stream-meta
limit: 30/min

Parameters

Name	Type	Req	Description
title	string	no	New stream title (1-140 characters)

game	string	no	Game/category name
kick_category_id	integer	no	Direct Kick category ID
platform	string	no	Kick or Twitch (default: Kick)

Example Request Body

```
{ "title": "New Title", "game": "Valorant" }
```

Example Success Response

```
{ "success": true, "title_updated": true, "game_updated": true, "title": "New Title", "category": "VALORANT", "viewer_count": 245, "followers_c
```

Alerts & Events - 4 endpoints

POST

Trigger Audio Alert

scope: trigger-audio-alert
limit: 60/min

<https://api.missxss.com.tr/v1/trigger-audio-alert>

Triggers an active audio alert by ID or name. Overlay connection is required.

Parameters

Name	Type	Req	Description
id	integer	no	Audio alert ID (id or name is required)
name	string	no	Audio alert name (id or name is required)
username	string	no	Username to display on alert (default: API)

Example Request Body

```
{ "id": 849, "name": "airhorn", "username": "api_bot" }
```

Example Success Response

```
{ "success": true, "id": 12, "alert_id": "A12", "name": "airhorn" }
```

POST

List Audio Alerts

scope: list-audio-alerts
limit: 90/min

<https://api.missxss.com.tr/v1/list-audio-alerts>

Lists audio alert records with ID, name and points.

Parameters

Name	Type	Req	Description
status	string	no	Filter: all active inactive (default: all)

<code>limit</code>	<code>integer</code>	<code>no</code>	Row count (1-200, default: 50)
<code>offset</code>	<code>integer</code>	<code>no</code>	Start offset (default: 0)

Example Request Body

```
{"status": "active", "limit": 20, "offset": 0}
```

Example Success Response

```
{"success": true, "total": 2, "limit": 20, "offset": 0, "alerts": [{"id": 14, "name": "airhorn", "points": 500, "status": "active"}]}
```

POST**Send Donation Simulation**

scope: send-donation
limit: 90/min

<https://api.missxss.com.tr/v1/send-donation>

Simulates donation flow for BynoGame, StreamElements, StreamLabs or Ko-fi, writes event log and triggers donation alert.

Parameters

Name	Type	Req	Description
<code>provider</code>	<code>string</code>	<code>yes</code>	BynoGame StreamElements StreamLabs Ko-fi
<code>amount</code>	<code>number</code>	<code>yes</code>	Donation amount (positive)
<code>currency</code>	<code>string</code>	<code>yes</code>	Currency Format (\$ EUR TRY ex.)
<code>username</code>	<code>string</code>	<code>no</code>	Donor username (default: api_donor)
<code>displayname</code>	<code>string</code>	<code>no</code>	Donor display name
<code>message</code>	<code>string</code>	<code>no</code>	Donation message
<code>userid</code>	<code>string</code>	<code>no</code>	Donor user ID (optional)
<code>platform</code>	<code>string</code>	<code>no</code>	Kick or Twitch (default: Kick)

Example Request Body

```
{"provider": "StreamLabs", "amount": 50, "currency": "TRY", "username": "viewer123", "displayname": "Viewer123", "message": "GG!"}
```

Example Success Response

```
{"success": true, "provider": "StreamLabs", "amount": 50, "currency": "TRY", "username": "viewer123", "displayname": "Viewer123", "message": "GG!"}
```

POST**Get Recent Activity**

scope: get-recent-activity
limit: 60/min

<https://api.missxss.com.tr/v1/get-recent-activity>

Returns latest followers, subscribers, banned users, donors, Kick bits and Twitch bits in a single request.

Parameters

Name	Type	Req	Description
limit	integer	no	Row count per list (1-20, default: 5)

Example Request Body

```
{"limit":5}
```

Example Success Response

```
{"success":true,"limit":5,"latest_followers":[],"latest_subscribers":[],"latest_banned":[],"latest_donors":[],"latest_kick_bits":["bits":[]]}
```

Effects - 1 endpoints

POST

Trigger Effect

scope: effect-trigger
limit: 120/min

<https://api.missxss.com.tr/v1/effect-trigger>

Triggers a trigger-enabled effect overlay through the API. The overlay receives action, overlay_id, effect_type, effect_settings and data; options is not sent. If data is omitted, only data.userstate is included by default.

Parameters

Name	Type	Req	Description
overlay_id	string	no	Effect overlay ID to trigger (overlay_id or overlay_ids is required)
overlay_ids	array	no	List of overlay IDs for bulk triggering (maximum 20)
platform	string	no	Default userstate platform: Kick, Twitch, YouTube or TikTok (default: Kick)
data	object	no	Custom JSON object passed to effect code. If omitted, only userstate is added; if provided, your fields are available under payload.data together with userstate.

Example Request Body

```
{"overlay_id":"effect_overlay_1","data":{"message":"API trigger","amount":100,"userstate":{"username":"api_user","displayname":"API User","platform":"Kick"}}
```

Example Success Response

```
{"success":true,"triggered":1,"total":1,"results":[{"overlay_id":"effect_overlay_1","success":true,"error":null}],"data_keys":["message","userstate"]}
```

Community Data - 1 endpoints

POST

List Kick Subscribers

scope: get-kick-subscribers
limit: 60/min<https://api.missxss.com.tr/v1/get-kick-subscribers>

Lists subscribers from kick_subscribers table. Returns only non-expired subscribers by default.

Parameters

Name	Type	Req	Description
include_expired	boolean string	no	Include expired subscribers when set to 1/true
limit	integer	no	Row count (1-200, default: 50)
offset	integer	no	Start offset (default: 0)

Example Request Body

```
{"include_expired":0,"limit":20,"offset":0}
```

Example Success Response

```
{"success":true,"total":12,"limit":20,"offset":0,"include_expired":0,"subscribers":[{"id":1,"kick_user_id":"123","kick_username":"Viewer","subscription_type":"self","tier":1}]}
```

Music & Song Request - 3 endpoints

POST

Start / Resume Song

scope: start-song
limit: 30/min<https://api.missxss.com.tr/v1/start-song>

Resumes a paused song or starts playback.

Parameters

Name	Type	Req	Description
No parameters. Send an empty JSON body or omit body.			

Example Request Body

```
{}
```

Example Success Response

```
{"success":true}
```

POST

Pause Song

<https://api.missxss.com.tr/v1/stop-song>

Pauses the currently playing song.

scope: stop-song
limit: 30/min

Parameters

Name	Type	Req	Description
No parameters. Send an empty JSON body or omit body.			

Example Request Body

```
{}
```

Example Success Response

```
{"success": true}
```

POST

Skip Song

<https://api.missxss.com.tr/v1/skip-song>

Skips the current song and plays the next one in queue.

scope: skip-song
limit: 30/min

Parameters

Name	Type	Req	Description
No parameters. Send an empty JSON body or omit body.			

Example Request Body

```
{}
```

Example Success Response

```
{"success": true}
```

Points & Economy - 6 endpoints

POST

Add Points

<https://api.missxss.com.tr/v1/add-points>

Adds points to target user. Resolves user by userid (Kick ID) first, then falls back to username.

scope: add-points
limit: 90/min

Parameters

Name	Type	Req	Description
------	------	-----	-------------

<code>userid</code>	<code>string</code>	<code>no</code>	Target user ID
<code>username</code>	<code>string</code>	<code>no</code>	Target username (without @). Used as fallback if userid is not found.
<code>amount</code>	<code>number</code>	<code>yes</code>	Points amount to add (1 - 99,999,999)
<code>platform</code>	<code>string</code>	<code>yes</code>	Required platform: Kick, Twitch, YouTube or TikTok

Example Request Body

```
{ "platform": "Kick", "userid": "123456", "username": "viewer123", "amount": 100 }
```

Example Success Response

```
{ "success": true }
```

POST

Remove Points

scope: remove-points
limit: 90/min

<https://api.missxss.com.tr/v1/remove-points>

Removes points from target user. Resolves by userid (Kick ID) first, then username fallback.

Parameters

Name	Type	Req	Description
<code>userid</code>	<code>string</code>	<code>no</code>	Target user ID
<code>username</code>	<code>string</code>	<code>no</code>	Target username (without @). Used as fallback if userid is not found.
<code>amount</code>	<code>number</code>	<code>yes</code>	Points amount to remove (1 - 99,999,999)
<code>platform</code>	<code>string</code>	<code>yes</code>	Required platform: Kick, Twitch, YouTube or TikTok

Example Request Body

```
{ "platform": "Kick", "userid": "123456", "username": "viewer123", "amount": 50 }
```

Example Success Response

```
{ "success": true }
```

POST

Get User Points

scope: get-points
limit: 120/min

<https://api.missxss.com.tr/v1/get-points>

Returns points/coin/message count for a user. Resolves by userid (Kick ID) first, then username fallback.

Parameters

Name	Type	Req	Description
------	------	-----	-------------

<code>userid</code>	<code>string</code>	<code>no</code>	Target user ID
<code>username</code>	<code>string</code>	<code>no</code>	Username (without @). Used as fallback if userid is not found.
<code>platform</code>	<code>string</code>	<code>yes</code>	Required platform: Kick, Twitch, YouTube or TikTok

Example Request Body

```
{ "platform": "Kick", "userid": "123456", "username": "viewer123" }
```

Example Success Response

```
{ "success": true, "platform": "Kick", "user_id": "123", "username": "viewer123", "displayname": "Viewer123", "points": 500, "coin": 25, "message": "" }
```

POST

Get Points Top

scope: get-points-top
limit: 90/min

<https://api.missxss.com.tr/v1/get-points-top>

Returns points leaderboard (supports limit/offset).

Parameters

Name	Type	Req	Description
<code>limit</code>	<code>integer</code>	<code>no</code>	Row count (1-100, default: 20)
<code>offset</code>	<code>integer</code>	<code>no</code>	Start offset (default: 0)
<code>platform</code>	<code>string</code>	<code>yes</code>	Required platform: Kick, Twitch, YouTube or TikTok

Example Request Body

```
{ "platform": "Kick", "limit": 10, "offset": 0 }
```

Example Success Response

```
{ "success": true, "platform": "Kick", "limit": 10, "offset": 0, "total": 1200, "users": [ { "rank": 1, "username": "topuser", "points": 999 } ] }
```

POST

Set Points Directly

scope: set-points
limit: 90/min

<https://api.missxss.com.tr/v1/set-points>

Sets user points to an exact value. Resolves by userid (Kick ID) first, then username fallback.

Parameters

Name	Type	Req	Description
<code>userid</code>	<code>string</code>	<code>no</code>	Target user ID
<code>username</code>	<code>string</code>	<code>no</code>	Username (without @). Used as fallback if userid is not found.

amount	integer	yes	New points value (0 - 99,999,999)
platform	string	yes	Required platform: Kick, Twitch, YouTube or TikTok

Example Request Body

```
{ "platform": "Kick", "userid": "123456", "username": "viewer123", "amount": 2500 }
```

Example Success Response

```
{ "success": true, "platform": "Kick", "username": "viewer123", "old_points": 1200, "points": 2500, "changed": 1300 }
```

POST

Transfer Points

scope: transfer-points
limit: 90/min

<https://api.missxss.com.tr/v1/transfer-points>

Transfers points from one user to another. For sender/receiver, userid is checked first, then username fallback.

Parameters

Name	Type	Req	Description
from_userid	string	no	Sender user ID
from_username	string	no	Sender username (without @), fallback
to_userid	string	no	Receiver user ID
to_username	string	no	Receiver username (without @), fallback
amount	integer	yes	Transfer amount (1 - 99,999,999)
platform	string	yes	Required platform: Kick, Twitch, YouTube or TikTok

Example Request Body

```
{ "platform": "Kick", "from_userid": "111", "from_username": "alice", "to_userid": "222", "to_username": "bob", "amount": 100 }
```

Example Success Response

```
{ "success": true, "platform": "Kick", "from_username": "alice", "from_user_id": "111", "to_username": "bob", "to_user_id": "222", "amount": 100 }
```

Watch Time - 4 endpoints

POST

Adjust Watch Time

scope: adjust-watch-time
limit: 60/min

<https://api.missxss.com.tr/v1/adjust-watch-time>

Adjusts watch time with add/remove/set modes. amount is in minutes. If day is omitted, an old fallback date is used to increase total stats without affecting current day.

Parameters

Name	Type	Req	Description
------	------	-----	-------------

<code>userid</code>	<code>string</code>	<code>no</code>	Target user ID
<code>username</code>	<code>string</code>	<code>no</code>	Target username (without @). Used as fallback if userid is not found.
<code>mode</code>	<code>string</code>	<code>yes</code>	Operation mode: add remove set
<code>amount</code>	<code>integer</code>	<code>yes</code>	Amount in minutes. min 1 for add/remove, min 0 for set (maximum 99,999,999 minutes)
<code>day</code>	<code>string</code>	<code>no</code>	Target day (YYYY-MM-DD). Fallback date is used when omitted.
<code>platform</code>	<code>string</code>	<code>yes</code>	Required platform: Kick, Twitch, YouTube or TikTok

Example Request Body

```
{ "platform": "Kick", "userid": "123456", "mode": "add", "amount": 30, "day": "2026-04-17" }
```

Example Success Response

```
{ "success": true, "platform": "Kick", "user_id": "123456", "username": "viewer123", "displayname": "Viewer123", "mode": "add", "amount": 30, "amount_unit": "minute", "day": "2026-04-17", "used_fallback_day": 0, "watch_time": 245, "watch_time_unit": "minute" }
```

POST

Get Watch Time

scope: get-watch-time
limit: 120/min

<https://api.missxss.com.tr/v1/get-watch-time>

Returns watch time and message count for a single user. Use day for one day, date_from/date_to for range, and omit date fields for all-time query.

Parameters

Name	Type	Req	Description
<code>userid</code>	<code>string</code>	<code>no</code>	Target user ID
<code>username</code>	<code>string</code>	<code>no</code>	Target username (without @). Used as fallback if userid is not found.
<code>day</code>	<code>string</code>	<code>no</code>	Single day filter (YYYY-MM-DD)
<code>date_from</code>	<code>string</code>	<code>no</code>	Range start date (YYYY-MM-DD), must be sent with date_to
<code>date_to</code>	<code>string</code>	<code>no</code>	Range end date (YYYY-MM-DD), must be sent with date_from
<code>platform</code>	<code>string</code>	<code>yes</code>	Required platform: Kick, Twitch, YouTube or TikTok

Example Request Body

```
{ "platform": "Kick", "userid": "123456", "day": "2026-04-17" }
```

Example Success Response

```
{ "success": true, "platform": "Kick", "user_id": "123456", "username": "viewer123", "displayname": "Viewer123", "query_mode": "day", "amount": 30, "amount_unit": "minute", "rom": null, "date_to": null, "watch_time": 245, "watch_time_unit": "minute", "message_count": 18 }
```

POST

Get Watch Time Top

scope: get-watch-time-top
limit: 90/min<https://api.missxss.com.tr/v1/get-watch-time-top>

Returns user leaderboard ordered by watch time. Supports filtering by day or date_from/date_to range.

Parameters

Name	Type	Req	Description
limit	integer	no	Row count (1-100, default: 20)
offset	integer	no	Start offset (default: 0)
day	string	no	Single day filter (YYYY-MM-DD)
date_from	string	no	Range start date (YYYY-MM-DD), must be sent with date_to
date_to	string	no	Range end date (YYYY-MM-DD), must be sent with date_from
platform	string	yes	Required platform: Kick, Twitch, YouTube or TikTok

Example Request Body

```
{ "platform": "Kick", "day": "2026-04-17", "limit": 10, "offset": 0 }
```

Example Success Response

```
{ "success": true, "platform": "Kick", "query_mode": "day", "day": "2026-04-17", "date_from": null, "date_to": null, "limit": 10, "offset": 0, "time_unit": "minute", "users": [ { "rank": 1, "user_id": "123456", "username": "viewer123", "displayname": "Viewer123", "watch_time": 245 } ], "message": "" }
```

POST

Adjust Watch Time Bulk

scope: adjust-watch-time-bulk
limit: 20/min<https://api.missxss.com.tr/v1/adjust-watch-time-bulk>

Adjusts watch time for multiple users in one request. amount is in minutes. You can set amount per user row; if omitted, request-level default amount is used.

Parameters

Name	Type	Req	Description
mode	string	yes	Operation mode: add remove set
day	string	no	Target day (YYYY-MM-DD). Fallback date is used when omitted.
amount	integer	no	Default amount in minutes. Used when users[].amount is missing.
users	array	yes	User list of 1-100 items. Each item must include userid or username and optional amount.
platform	string	yes	Required platform: Kick, Twitch, YouTube or TikTok

Example Request Body

```
{ "platform": "Kick", "mode": "add", "day": "2026-04-17", "users": [ { "userid": "123456", "amount": 30 }, { "username": "viewer2", "amount": 15 } ] }
```

Example Success Response

```
{ "success":true, "partial":0, "platform":"Kick", "mode":"add", "day":"2026-04-17", "used_fallback_day":0, "amount_unit":"minute", "total_requested":2, "processed_count":2, "failed_count":0, "users":[{"index":0, "user_id":"123456", "username":"viewer123", "mode":"add", "amount":30, "day":"2026-04-17", "watch_time":245, "message_count":18}], "failed":[] }
```

Command Management - 8 endpoints

POST

Run Command

scope: run-command

limit: 90/min

<https://api.missxss.com.tr/v1/run-command>

Runs a chat command you defined in the MissXss panel. Can be called by command name or command ID. The command response message is sent and its actions (timeout, ban, voicemod etc.) are automatically processed.

Parameters

Name	Type	Req	Description
command	string	no	Command name (e.g. "!hello" or "hello"). command or id is required.
id	integer	no	Command ID value. command or id is required.
message	string	no	Additional message / arguments to append to the command
username	string	no	Username running the command (default: broadcaster name)

Example Request Body

```
{ "command": "!hello" }
```

Example Success Response

```
{ "success":true, "id":22029, "command":"!hello", "active":1, "response":"Hello everyone!" }
```

POST

List Commands (Detailed)

scope: list-commands

limit: 90/min

<https://api.missxss.com.tr/v1/list-commands>

Returns all commands for the broadcaster with detailed fields and can be used to discover command IDs for run-command and toggle-command. Response fields: total=total command count; commands[]=command list; id=command ID; command=primary command name; aliases=alternative triggers; active=enabled flag (1/0); show_in_list=show in command list; cooldown_global_seconds=global cooldown; cooldown_user_seconds=user cooldown; message=command response text; permissions=allowed roles/permissions; denied_permissions=blocked roles/permissions; action_json=command action JSON; platform_kick/platform_twitch/platform_tiktok/platform_youtube=platform enable flags; auto_message_interval_minutes=auto-send interval in minutes; auto_message_min_chat_count=minimum chat messages before next auto-send; last_run_at=last run timestamp; last_global_run_at=last global run timestamp; last_user_run_data=per-user last run data; points_cost/coin_cost/delete_cost=command costs; only_game_ids=allowed category/game IDs; blocked_game_ids=blocked category/game IDs; last_auto_message_kick_at/last_auto_message_twitch_at=last auto-send timestamps by platform; raw=raw in-memory command object.

Parameters

Name	Type	Req	Description
No parameters. Send an empty JSON body or omit body.			

Example Request Body

```
{}
```

Example Success Response

```
{ "success": true, "total": 2, "commands": [ { "id": 22029, "command": "!hello", "aliases": [ "!hello", "hello" ], "active": 1, "show_in_list": 0, "cooldown_user_seconds": 0, "message": "Hello!", "permissions": "", "denied_permissions": "", "action_json": "", "platform_kick": 1, "platform_tiktok": 1, "platform_youtube": 1, "auto_message_interval_minutes": 0, "auto_message_min_chat_count": 0, "last_run_at": "2026-07-02 22:01:00" } ] }
```

POST

Toggle Command

scope: toggle-command
limit: 60/min

<https://api.missxss.com.tr/v1/toggle-command>

Enables, disables, or toggles a command by name or ID. mode value: on | off | toggle.

Parameters

Name	Type	Req	Description
<code>command</code>	<code>string</code>	no	Command name. command or id is required.
<code>id</code>	<code>integer</code>	no	Command ID value. command or id is required.
<code>mode</code>	<code>string</code>	yes	Mode: on off toggle

Example Request Body

```
{ "id": 22029, "mode": "off" }
```

Example Success Response

```
{ "success": true, "id": 22029, "command": "!hello", "active": 0, "changed": true, "mode": "off" }
```

POST

Create Command

scope: create-command
limit: 60/min

<https://api.missxss.com.tr/v1/create-command>

Creates a new command and adds it to command list.

Parameters

Name	Type	Req	Description
<code>command</code>	<code>string</code>	yes	Command name (max 50 chars)
<code>message</code>	<code>string</code>	yes	Command response message

Example Request Body

```
{ "command": "!hi", "message": "Hello everyone!" }
```

Example Success Response

```
{"success":true,"id":22035,"command":"!hi","aliases":["!hi"],"active":1}
```

POST

Update Command

scope: update-command
limit: 60/min<https://api.missxss.com.tr/v1/update-command>

Updates command message and/or aliases.

Parameters

Name	Type	Req	Description
<code>command</code>	<code>string</code>	no	Command name (command or id required)
<code>id</code>	<code>integer</code>	no	Command ID (command or id required)
<code>message</code>	<code>string</code>	no	New command response
<code>aliases</code>	<code>string array</code>	no	New aliases (comma string or array)

Example Request Body

```
{"id":22035,"message":"Hello there!"}
```

Example Success Response

```
{"success":true,"id":22035,"command":"!hi","aliases":["!hi","!hello"],"message":"Hello there!"}
```

POST

Delete Command

scope: delete-command
limit: 60/min<https://api.missxss.com.tr/v1/delete-command>

Deletes command by name or ID.

Parameters

Name	Type	Req	Description
<code>command</code>	<code>string</code>	no	Command name (command or id required)
<code>id</code>	<code>integer</code>	no	Command ID (command or id required)

Example Request Body

```
{"id":22035}
```

Example Success Response

```
{"success":true,"deleted":true,"command":"selam","id":22035}
```

POST

Set Command Cooldown

scope: set-command-cooldown
limit: 60/min<https://api.missxss.com.tr/v1/set-command-cooldown>

Sets global and user cooldown values for command.

Parameters

Name	Type	Req	Description
<code>command</code>	<code>string</code>	no	Command name (command or id required)
<code>id</code>	<code>integer</code>	no	Command ID (command or id required)
<code>cooldown_global_seconds</code>	<code>integer</code>	no	Global cooldown seconds (0-86400)
<code>cooldown_user_seconds</code>	<code>integer</code>	no	User cooldown seconds (0-86400)

Example Request Body

```
{"id":22029,"cooldown_global_seconds":10,"cooldown_user_seconds":30}
```

Example Success Response

```
{"success":true,"id":22029,"command":"hello","cooldown_global_seconds":10,"cooldown_user_seconds":30}
```

POST

Set Command Platforms

scope: set-command-platforms
limit: 60/min<https://api.missxss.com.tr/v1/set-command-platforms>

Updates command platform enable flags.

Parameters

Name	Type	Req	Description
<code>command</code>	<code>string</code>	no	Command name (command or id required)
<code>id</code>	<code>integer</code>	no	Command ID (command or id required)
<code>platform_kick</code>	<code>boolean integer</code>	no	Kick active flag (1/0)
<code>platform_twitch</code>	<code>boolean integer</code>	no	Twitch active flag (1/0)
<code>platform_tiktok</code>	<code>boolean integer</code>	no	TikTok active flag (1/0)
<code>platform_youtube</code>	<code>boolean integer</code>	no	YouTube active flag (1/0)

Example Request Body

```
{"id":22029,"platform_kick":1,"platform_twitch":0,"platform_youtube":1}
```

Example Success Response

```
{"success":true,"id":22029,"command":"hello","platform_kick":1,"platform_twitch":0,"platform_tiktok":1,"platform_youtube":1}
```

AI Bot - 2 endpoints

POST

Update AI Bot Settings

scope: ai-bot
limit: 20/min<https://api.missxss.com.tr/v1/ai-bot>

Updates AI Bot settings independently. You can send any single field alone. Supports on/off/toggle for gemini_aktif and ai_sadeceAbone. If ai_text changes, conversation history is automatically cleared.

Parameters

Name	Type	Req	Description
gemini_aktif	string	no	AI Bot state: on off toggle
ai_sadeceAbone	string	no	Subscriber-only mode: on off toggle
ai_text	string	no	AI Bot prompt text (max 12000 characters)

Example Request Body

```
{"gemini_aktif": "on"}
```

Example Success Response

```
{"success": true, "gemini_aktif": 1, "ai_sadeceAbone": 0, "ai_text_updated": true, "clearai_triggered": false}
```

POST

Clear AI Conversation History

scope: clear-ai
limit: 10/min<https://api.missxss.com.tr/v1/clear-ai>

Clears AI conversation history. API equivalent of !clearai command.

Parameters

Name	Type	Req	Description
No parameters. Send an empty JSON body or omit body.			

Example Request Body

```
{}
```

Example Success Response

```
{"success": true, "cleared": true}
```

Moderation - 11 endpoints

POST

Timeout

scope: timeout
limit: 200/min<https://api.missxss.com.tr/v1/timeout>

Times out a user for a specified duration. Duration is in minutes (maximum 525600 minutes = 1 year).

Parameters

Name	Type	Req	Description
<code>username</code>	<code>string</code>	yes	Username to timeout
<code>duration</code>	<code>integer</code>	no	Duration (minutes). Min: 1, Max: 525600. Default: 1
<code>reason</code>	<code>string</code>	no	Timeout reason (default: "API Timeout")
<code>platform</code>	<code>string</code>	no	Kick or Twitch (default: Kick)

Example Request Body

```
{"username": "troll_user", "duration": 5, "reason": "Spamming"}
```

Example Success Response

```
{"success": true}
```

POST

Ban

scope: ban
limit: 200/min<https://api.missxss.com.tr/v1/ban>

Permanently bans a user. Use with caution.

Parameters

Name	Type	Req	Description
<code>username</code>	<code>string</code>	yes	Username to ban
<code>userid</code>	<code>string</code>	no	User ID to ban. If sent with username, userid is used preferentially.
<code>reason</code>	<code>string</code>	no	Ban reason (default: "API Ban")
<code>platform</code>	<code>string</code>	no	Kick or Twitch (default: Kick)

Example Request Body

```
{"username": "bad_user", "reason": "Rule violation"}
```

Example Success Response

```
{"success": true}
```

POST

Clear Chat

<https://api.missxss.com.tr/v1/clear-chat>

Clears all chat messages.

scope: clear-chat
limit: 15/min

Parameters

Name	Type	Req	Description
No parameters. Send an empty JSON body or omit body.			

Example Request Body

```
{}
```

Example Success Response

```
{"success": true}
```

POST

Manage Shield Mode

<https://api.missxss.com.tr/v1/shield-mode>

Turns shield mode on, off, or toggles it. mode parameter: on, off, toggle.

scope: shield-mode
limit: 15/min

Parameters

Name	Type	Req	Description
mode	string	no	Operation mode: on off toggle (default: toggle)
duration	integer	no	Shield-ban lookback window in minutes (min: 0). Used only when enabling/toggle->on.

Example Request Body

```
{"mode": "on" }
```

Example Success Response

```
{"success": true, "shield_mode": 1, "changed": true, "mode": "on" }
```

POST

Get Shield Mode Status

<https://api.missxss.com.tr/v1/get-shield-mode-status>

Returns current shield mode configuration.

scope: get-shield-mode-status
limit: 90/min

Parameters

Name	Type	Req	Description
No parameters. Send an empty JSON body or omit body.			

Example Request Body

```
{}
```

Example Success Response

```
{"success":true,"shield_mode":1,"shield_ban_enabled":1,"shield_lookback_minutes":2}
```

POST

Set Moderation Feature

scope: set-moderation-feature
limit: 10/min

<https://api.missxss.com.tr/v1/set-moderation-feature>

Enables, disables, or toggles a specific moderation feature.

Parameters

Name	Type	Req	Description
feature	string	yes	username_kontrol, spam_korumasi, link_korumasi, kufur_korumasi, caps_korumasi, flood_korumasi, coklu_hesap_spam, ziyaretci_kontrol
mode	string	yes	on off toggle

Example Request Body

```
{"feature":"spam_korumasi","mode":"on"}
```

Example Success Response

```
{"success":true,"feature":"spam_korumasi","enabled":1,"changed":true,"mode":"on"}
```

POST

Get Moderation Status

scope: get-moderation-status
limit: 90/min

<https://api.missxss.com.tr/v1/get-moderation-status>

Returns enabled/disabled state for moderation modules. If feature is provided, returns single module status.

Parameters

Name	Type	Req	Description
feature	string	no	Optional single feature name

Example Request Body

```
{}
```

Example Success Response

```
{"success":true,"status":{"username_kontrol":1,"spam_korumasi":1,"link_korumasi":1,"kufur_korumasi":1,"caps_korumasi":1,"flood_korumasi":1,"coklu_hesap_spam":0,"ziyaretci_kontrol":1,"kalkan_modu":0,"kalkan_ban":1,"kalkan_sure":2}}
```

POST

Get Platform Ban List

scope: get-platform-ban-list
limit: 60/min<https://api.missxss.com.tr/v1/get-platform-ban-list>

Lists ban records from platform_ban_list table.

Parameters

Name	Type	Req	Description
platform	string	no	Kick Twitch YouTube TikTok (optional filter)
limit	integer	no	Row count (1-200, default: 50)
offset	integer	no	Start offset (default: 0)

Example Request Body

```
{"platform": "Kick", "limit": 20, "offset": 0}
```

Example Success Response

```
{"success": true, "total": 8, "limit": 20, "offset": 0, "platform": "Kick", "bans": [{"id": 15, "platform": "Kick", "banned_id": "123", "banned_user": "user1", "reason": "spam"}]}
```

POST

Get Moderation Log

scope: get-moderation-log
limit: 60/min<https://api.missxss.com.tr/v1/get-moderation-log>

Returns moderation records from event table. Source: event records written by eventlog().

Parameters

Name	Type	Req	Description
type	string	no	Filter: all ban timeout shield (default: all)
limit	integer	no	Row count (1-50, default: 25)
offset	integer	no	Start offset (default: 0)

Example Request Body

```
{"type": "all", "limit": 25, "offset": 0}
```

Example Success Response

```
{"success": true, "source": "event", "type": "all", "limit": 25, "offset": 0, "logs": [{"id": 991, "type": "Timeout", "username": "user1", "date": "2026-07-02 14:20:00"}]}
```

POST

Unban User

<https://api.missxss.com.tr/v1/unban-user>

Removes ban for specified user.

scope: unban-user
limit: 60/min

Parameters

Name	Type	Req	Description
username	string	yes	Username to unban
platform	string	no	Kick or Twitch (default: Kick)

Example Request Body

```
{ "username": "old_banned_user" }
```

Example Success Response

```
{ "success": true, "username": "old_banned_user", "platform": "Kick" }
```

POST

Ban Recent Followers

<https://api.missxss.com.tr/v1/ban-recent-followers>

Quickly ban/timeout the most recent followers. Can ban up to 10 users at once. offset parameter specifies starting position (1 = most recent), count parameter specifies how many users to ban.

scope: ban-recent-followers
limit: 200/min

Parameters

Name	Type	Req	Description
action	string	yes	ban or timeout
offset	integer	no	Starting position (1 = most recent; default: 1)
count	integer	no	How many users to process (1-10; default: 1)
duration	integer	no	Timeout duration in minutes, only for action=timeout (min: 1, max: 525600; default: 1)
reason	string	no	Reason for action (default: "API Ban Recent")
platform	string	no	Kick or Twitch (default: Kick)

Example Request Body

```
{ "action": "ban", "offset": 1, "count": 2, "reason": "Spam" }
```

Example Success Response

```
{ "success": true, "action": "ban", "processed_count": 2, "users": [ { "username": "user1", "userid": "123" }, { "username": "user2", "userid": "456" } ] }
```

Discord Core - 3 endpoints

POST

Discord Status

scope: discord-status
limit: 90/min<https://api.missxss.com.tr/v1/discord-status>

Returns Discord bot connection status, guild/channel availability and core permissions.

Parameters

Name	Type	Req	Description
<code>guild_id</code>	<code>string</code>	no	Discord guild ID (read from active settings if omitted)
<code>channel_id</code>	<code>string</code>	no	Discord message channel ID (optional check)
<code>log_channel_id</code>	<code>string</code>	no	Discord log channel ID (optional check)

Example Request Body

```
{"guild_id": "123456789012345678" }
```

Example Success Response

```
{"success": true, "bot_connected": true, "guild_found": true, "channel_found": true, "permissions": {"manage_roles": true, "move_members": true}}
```

POST

Discord Send Message

scope: discord-send-message
limit: 30/min<https://api.missxss.com.tr/v1/discord-send-message>

Sends text or embed message to your Discord guild channel. Channel ID is required and must belong to your configured guild for security.

Parameters

Name	Type	Req	Description
<code>channel_id</code>	<code>string</code>	yes	Target Discord channel ID (required, must belong to your guild)
<code>message</code>	<code>string</code>	no	Text message to send (max 2000 characters)
<code>embed_title</code>	<code>string</code>	no	Embed title (max 256 characters)
<code>embed_description</code>	<code>string</code>	no	Embed description (max 4096 characters)
<code>embed_color</code>	<code>string</code>	no	Embed color (hex: #FF5733 or decimal: 16721715)

Example Request Body

```
{"channel_id": "1383215007457611957", "message": "Merhaba Discord!"}
```

Example Success Response

```
{"success": true, "channel_id": "1383215007457611957", "guild_id": "700705230106394645", "message_id": "1445427371040571642" }
```

POST

List Discord Linked Users

scope: discord-linked-users
limit: 90/min<https://api.missxss.com.tr/v1/discord-linked-users>

Returns paginated Discord-Kick/Twitch linked user records for this broadcaster.

Parameters

Name	Type	Req	Description
limit	integer	no	Records per page (1-200, default 50)
offset	integer	no	Start offset (default 0)

Example Request Body

```
{"limit":50,"offset":0}
```

Example Success Response

```
{"success":true,"total":120,"limit":50,"offset":0,"users":[{"id":1,"discord_id":"123","kick_id":"456","twitch_id":"789"}]}
```

Discord Voice Controls - 7 endpoints

POST

List Discord Voice Members

scope: discord-voice-members
limit: 90/min<https://api.missxss.com.tr/v1/discord-voice-members>

Returns all voice channels in a guild or members of a specific voice channel. Guild ID is automatically resolved from account settings.

Parameters

Name	Type	Req	Description
channel_id	string	no	Voice channel ID to filter a single channel

Example Request Body

```
{}
```

Example Success Response

```
{"success":true,"guild_id":"123456789012345678","total_channels":2,"channels":[{"id":"111","name":"Genel","member_count":...}]}
```

POST

Discord Voice Kick User

scope: discord-voice-kick
limit: 30/min<https://api.missxss.com.tr/v1/discord-voice-kick>

Disconnects the specified user from their current voice channel. Guild ID is automatically resolved from account settings (security).

Parameters

Name	Type	Req	Description
------	------	-----	-------------

<code>discord_id</code>	<code>string</code>	<code>yes</code>	Discord user ID to disconnect
-------------------------	---------------------	------------------	-------------------------------

Example Request Body

```
{"discord_id": "55555555555555555555"}
```

Example Success Response

```
{"success": true, "discord_id": "55555555555555555555", "kicked": true}
```

POST**Discord Voice Move User**

scope: discord-voice-move
limit: 30/min

<https://api.missxss.com.tr/v1/discord-voice-move>

Moves the specified user to the target voice channel. Guild ID is automatically resolved from account settings (security).

Parameters

Name	Type	Req	Description
<code>discord_id</code>	<code>string</code>	<code>yes</code>	Discord user ID to move
<code>target_channel_id</code>	<code>string</code>	<code>yes</code>	Target voice channel ID

Example Request Body

```
{"discord_id": "55555555555555555555", "target_channel_id": "99999999999999999999"}
```

Example Success Response

```
{"success": true, "discord_id": "55555555555555555555", "target_channel_id": "99999999999999999999", "moved": true}
```

POST**Discord Voice Mute/Unmute User**

scope: discord-voice-mute
limit: 30/min

<https://api.missxss.com.tr/v1/discord-voice-mute>

Mutes, unmutes, or toggles mute state for the specified user. Guild ID is automatically resolved from account settings (security).

Parameters

Name	Type	Req	Description
<code>discord_id</code>	<code>string</code>	<code>yes</code>	Discord user ID
<code>mode</code>	<code>string</code>	<code>no</code>	on off toggle (default: toggle)

Example Request Body

```
{"discord_id": "55555555555555555555", "mode": "on"}
```

Example Success Response

```
{"success": true, "discord_id": "55555555555555555555", "muted": true, "changed": true, "mode": "on"}
```

POST

Discord Voice Mute All

scope: discord-voice-mute-all
limit: 30/min<https://api.missxss.com.tr/v1/discord-voice-mute-all>

Mutes all non-bot users in the specified voice channel. Guild ID is automatically resolved from account settings (security).

Parameters

Name	Type	Req	Description
<code>channel_id</code>	<code>string</code>	yes	Voice channel ID

Example Request Body

```
{"channel_id": "999999999999999999"}
```

Example Success Response

```
{"success": true, "channel_id": "999999999999999999", "muted_count": 6}
```

POST

Discord Voice Unmute All

scope: discord-voice-unmute-all
limit: 30/min<https://api.missxss.com.tr/v1/discord-voice-unmute-all>

Unmutes all non-bot users in the specified voice channel. Guild ID is automatically resolved from account settings (security).

Parameters

Name	Type	Req	Description
<code>channel_id</code>	<code>string</code>	yes	Voice channel ID

Example Request Body

```
{"channel_id": "999999999999999999"}
```

Example Success Response

```
{"success": true, "channel_id": "999999999999999999", "unmuted_count": 6}
```

POST

Discord Voice Pull All

scope: discord-voice-pull-all
limit: 30/min<https://api.missxss.com.tr/v1/discord-voice-pull-all>

Pulls users into one room. If `from_channel_id` is provided, only users in that channel are moved; otherwise users from all voice channels are moved to `target_channel_id`. Guild ID is automatically resolved from account settings (security).

Parameters

Name	Type	Req	Description
<code>target_channel_id</code>	<code>string</code>	yes	Target voice channel ID

<code>from_channel_id</code>	<code>string</code>	<code>no</code>	Source voice channel ID (optional)
------------------------------	---------------------	-----------------	------------------------------------

Example Request Body

```
{"target_channel_id": "9999999999999999"}
```

Example Success Response

```
{"success": true, "target_channel_id": "9999999999999999", "source_channel_id": null, "moved_count": 4}
```

Voicemod - 3 endpoints

POST

Change Voice

scope: voicemod-voice-change
limit: 60/min<https://api.missxss.com.tr/v1/voicemod-voice-change>

Changes the voice effect via Voicemod. Overlay connection required.

Parameters

Name	Type	Req	Description
<code>voice</code>	<code>string</code>	yes	Voice effect name (e.g. "baby", "deep")
<code>wait_time</code>	<code>integer</code>	<code>no</code>	Effect duration (seconds, default: 60)
<code>original_voice</code>	<code>integer</code>	<code>no</code>	Return to original voice after duration (0 or 1, default: 0)

Example Request Body

```
{"voice": "baby", "wait_time": 60}
```

Example Success Response

```
{"success": true}
```

POST

Play Sound Effect

scope: voicemod-effect-play
limit: 60/min<https://api.missxss.com.tr/v1/voicemod-effect-play>

Plays a Voicemod meme sound effect (soundboard).

Parameters

Name	Type	Req	Description
<code>voice</code>	<code>string</code>	yes	Effect name

Example Request Body

```
{"voice": "applause"}
```

Example Success Response

```
{"success":true}
```

POST

Hear My Self

scope: voicemod-hear-self
limit: 60/min

<https://api.missxss.com.tr/v1/voicemod-hear-self>

Activates the Voicemod "Hear My Self" feature for a specified duration.

Parameters

Name	Type	Req	Description
<code>wait_time</code>	<code>integer</code>	no	Duration (seconds, default: 60)

Example Request Body

```
{"wait_time":120}
```

Example Success Response

```
{"success":true}
```