

MissXss API AI Reference

This document is generated so AI tools can understand MissXss API endpoints, parameters, scope requirements, and request/response examples.

Base URL https://api.missxss.com.tr	Authentication Bearer	Endpoints 64
--	---------------------------------	------------------------

Quick Start

- Use Authorization: Bearer YOUR_API_KEY on every request.
- Send POST requests to <https://api.missxss.com.tr/v1/{scope}>.
- Use Content-Type: application/json and include only the parameters listed for the endpoint.

Chat & Messaging - 3 endpoints

POST

Send Message (As Broadcaster)

<https://api.missxss.com.tr/v1/send-message>

Sends a chat message as the broadcaster account. The message appears under your own name.

scope: send-message
limit: 90/min

Parameters

Name	Type	Req	Description
message	string	yes	Message text to send (1-500 characters)
platform	string	no	Target platform: Kick or Twitch (default: Kick)

Example Request Body

```
{"message": "Hello Chat!"}
```

Example Success Response

```
{"success": true, "message_id": "abc123"}
```

POST

Send Message (As Bot)

<https://api.missxss.com.tr/v1/send-bot-message>

Sends a chat message via the MissXss bot account. The message appears under the bot name.

scope: send-bot-message
limit: 90/min

Parameters

Name	Type	Req	Description
------	------	-----	-------------

message	string	yes	Message text to send (1-500 characters)
platform	string	no	Target platform: Kick or Twitch (default: Kick)

Example Request Body

```
{"message":"This is a bot message!"}
```

Example Success Response

```
{"success":true,"message_id":"def456"}
```

POST

Send TTS Message

<https://api.missxss.com.tr/v1/tts>

Reads a text-to-speech message on stream. The overlay must be connected. A per-minute rate limit applies.

scope: tts
limit: 20/min

Parameters

Name	Type	Req	Description
text	string	yes	Text to speak (1-500 characters)
username	string	no	Display username shown on screen (default: "API")

Example Request Body

```
{"text":"Hello Stream!","username":"Bot"}
```

Example Success Response

```
{"success":true,"ttsId":"a1b2c3d4..."}
```

Stream Controls - 6 endpoints

POST

Create Clip

<https://api.missxss.com.tr/v1/clip>

Creates a clip from the current live stream. Works via extension connection on Kick and API on Twitch. Stream must be live.

scope: clip
limit: 20/min

Parameters

Name	Type	Req	Description
title	string	no	Clip title (default: "Clip - MissXss API")
duration	integer	no	Clip duration (5-180 seconds, default: 30)
platform	string	no	Kick or Twitch to create a clip only on that platform. If omitted or set to all, clips are created on all live platforms.

send_chat_message	boolean	no	Sends the clip link to chat. If false, no chat message is sent on any platform (default: true).
-------------------	---------	----	---

Example Request Body

```
{"title":"Epic moment!","duration":45,"platform":"all","send_chat_message":true}
```

Example Success Response

```
{"success":true,"platform":"all","send_chat_message":true,"clips":{"kick":"https://kick.com/channel/clips/clip_id","twitch":"https://twitch.com/channel/clips/clip_id"},"platforms":{"kick":"created","twitch":"created"}}
```

POST

Change Game / Category

<https://api.missxss.com.tr/v1/game>

Changes the stream category. If platform is omitted, Kick and Twitch are updated together; if provided, only the selected platform is updated. You can send a game name or Kick category ID; if both are sent, ID takes priority.

scope: game
limit: 20/min

Parameters

Name	Type	Req	Description
game	string	no	Game/category name (e.g. "Valorant"). Required if kick_category_id is not sent.
kick_category_id	integer	no	Kick category ID. Sending the ID directly is faster if known.
platform	string	no	Kick or Twitch to update only one platform. If omitted, both are updated.

Example Request Body

```
{"game":"Valorant"}
```

Example Success Response

```
{"success":true,"game":"VALORANT","platform":"all"}
```

POST

Smart Game / Category Search

<https://api.missxss.com.tr/v1/search-games>

Performs a smart search in the game database. Exact name match, slug match, starts-with match, word containment and spelling similarity are scored together; closest games are returned based on similarity ratio.

scope: search-games
limit: 40/min

Parameters

Name	Type	Req	Description
query	string	yes	Game/category name to search (2-100 chars). game or search is also accepted.
limit	integer	no	Maximum row count to return (1-50, default: 10)
min_similarity	number	no	Minimum similarity score (0-100, default: 25)

Example Request Body

```
{"query": "banana", "limit": 10}
```

Example Success Response

```
{ "success": true, "query": "banana", "total": 3, "best_match": { "kick_category_id": 123, "name": "Banana", "slug": "banana", "score": 100, "match_type": "exact_name" }, "games": [ { "kick_category_id": 123, "name": "Banana", "slug": "banana", "score": 100, "match_type": "exact_name" } ] }
```

POST

Change Stream Title

<https://api.missxss.com.tr/v1/title>

Changes the stream title. If platform is omitted, connected Kick, Twitch and YouTube accounts are updated; if provided, only the selected platform is updated.

scope: title
limit: 20/min

Parameters

Name	Type	Req	Description
title	string	yes	New stream title (1-140 characters)
platform	string	no	Kick, Twitch or YouTube to update only one platform. If omitted, all are updated.

Example Request Body

```
{"title": "New stream title!"}
```

Example Success Response

```
{"success": true, "platform": "all"}
```

POST

Get Stream Meta

<https://api.missxss.com.tr/v1/get-stream-meta>

Returns stream metadata via POST method, including viewer_count and followers_count.

scope: get-stream-meta
limit: 120/min

Parameters

Name	Type	Req	Description
platform	string	no	Kick or Twitch (default: Kick)

Example Request Body

```
{}
```

Example Success Response

```
{ "success": true, "platform": "Kick", "channel": "kanaladi", "title": "Live Stream", "category": "Just Chatting", "category_id": "123", "viewer_count": 245, "followers_count": 19234, "is_live_any": 1, "is_live_kick": 1, "is_live_twitch": 0, "kick_id": "2026-04-18" }
```

POST

Set Stream Meta

<https://api.missxss.com.tr/v1/set-stream-meta>

Updates title and/or game metadata in one request. If platform is omitted, all supported platforms are updated; if provided, only the selected platform is updated. At least one of title, game or kick_category_id must be provided.

scope: set-stream-meta

limit: 30/min

Parameters

Name	Type	Req	Description
title	string	no	New stream title (1-140 characters)
game	string	no	Game/category name
kick_category_id	integer	no	Direct Kick category ID
platform	string	no	Kick, Twitch, or YouTube for title-only updates. If omitted, all supported platforms are updated.

Example Request Body

```
{"title": "New Title", "game": "Valorant"}
```

Example Success Response

```
{"success": true, "platform": "all", "title_updated": true, "game_updated": true, "title": "New Title", "category": "VALORANT", "viewer_count": 245, "followers_count": 19234}
```

Alerts & Events - 4 endpoints

POST

Trigger Audio Alert

<https://api.missxss.com.tr/v1/trigger-audio-alert>

Triggers an active audio alert by ID or name. Overlay connection is required.

scope: trigger-audio-alert

limit: 60/min

Parameters

Name	Type	Req	Description
id	integer	no	Audio alert ID (id or name is required)
name	string	no	Audio alert name (id or name is required)
username	string	no	Username to display on alert (default: API)

Example Request Body

```
{"id": 849, "name": "airhorn", "username": "api_bot"}
```

Example Success Response

```
{"success": true, "id": 12, "alert_id": "A12", "name": "airhorn"}
```

POST

List Audio Alerts

<https://api.missxss.com.tr/v1/list-audio-alerts>

Lists audio alert records with ID, name and points.

scope: list-audio-alerts
limit: 90/min

Parameters

Name	Type	Req	Description
status	string	no	Filter: all active inactive (default: all)
limit	integer	no	Row count (1-200, default: 50)
offset	integer	no	Start offset (default: 0)

Example Request Body

```
{"status": "active", "limit": 20, "offset": 0}
```

Example Success Response

```
{"success": true, "total": 2, "limit": 20, "offset": 0, "alerts": [{"id": 14, "name": "airhorn", "points": 500, "status": "active"}]}
```

POST

Send Donation Simulation

<https://api.missxss.com.tr/v1/send-donation>

Simulates donation flow for BynoGame, StreamElements, StreamLabs or Ko-fi, writes event log and triggers donation alert.

scope: send-donation
limit: 90/min

Parameters

Name	Type	Req	Description
provider	string	yes	BynoGame StreamElements StreamLabs Ko-fi
amount	number	yes	Donation amount (positive)
currency	string	yes	Currency Format (\$ EUR TRY ex.)
username	string	no	Donor username (default: api_donor)
displayname	string	no	Donor display name
message	string	no	Donation message
userid	string	no	Donor user ID (optional)
platform	string	no	Kick or Twitch (default: Kick)

Example Request Body

```
{"provider": "StreamLabs", "amount": 50, "currency": "TRY", "username": "viewer123", "displayname": "Viewer123", "message": "GG!"}
```

Example Success Response

```
{\\"success\\": true, \\"provider\\": \\"StreamLabs\\", \\"amount\\": 50, \\"currency\\" => \\"TRY\\", \\"username\\": \\"viewer123\\", \\"displayname\\": \\"Viewer123\\", \\"message\\": \\"GG!\\\"}
```

POST

Get Recent Activity

<https://api.missxss.com.tr/v1/get-recent-activity>

Returns latest followers, subscribers, banned users, donors, Kick bits and Twitch bits in a single request.

scope: get-recent-activity
limit: 60/min

Parameters

Name	Type	Req	Description
limit	integer	no	Row count per list (1-20, default: 5)

Example Request Body

```
{"limit":5}
```

Example Success Response

```
{\"success\":true,\"limit\":5,\"latest_followers\":[],\"latest_subscribers\":[],\"latest_banned\":[],\"latest_donors\":[],\"latest_kick_bits\":[],\"latest_twitch_bits\":[]}
```

Effects - 1 endpoints

POST

Trigger Effect

<https://api.missxss.com.tr/v1/effect-trigger>

Triggers a trigger-enabled effect overlay through the API. The overlay receives action, overlay_id, effect_type, effect_settings and data; options is not sent. If data is omitted, only data.userstate is included by default.

scope: effect-trigger
limit: 120/min

Parameters

Name	Type	Req	Description
overlay_id	string	no	Effect overlay ID to trigger (overlay_id or overlay_ids is required)
overlay_ids	array	no	List of overlay IDs for bulk triggering (maximum 20)
platform	string	no	Default userstate platform: Kick, Twitch, YouTube or TikTok (default: Kick)
data	object	no	Custom JSON object passed to effect code. If omitted, only userstate is added; if provided, your fields are available under payload.data together with userstate.

Example Request Body

```
{\"overlay_id\":\"effect_overlay_1\",\"data\":{\"message\":\"API trigger\",\"amount\":100,\"userstate\":{\"username\":\"api_user\",\"displayname\":\"API User\",\"platform\":\"Kick\"}}}
```

Example Success Response

```
{
  "success": true,
  "triggered": 1,
  "total": 1,
  "results": [
    {
      "overlay_id": "effect_overlay_1",
      "success": true,
      "error": null
    }
  ],
  "data_keys": [
    "me",
    "userstate"
  ]
}
```

Community Data - 1 endpoints

POST

List Kick Subscribers

<https://api.missxss.com.tr/v1/get-kick-subscribers>

Lists subscribers from kick_subscribers table. Returns only non-expired subscribers by default.

scope: get-kick-subscribers

limit: 60/min

Parameters

Name	Type	Req	Description
include_expired	boolean string	no	Include expired subscribers when set to 1/true
limit	integer	no	Row count (1-200, default: 50)
offset	integer	no	Start offset (default: 0)

Example Request Body

```
{
  "include_expired": 0,
  "limit": 20,
  "offset": 0
}
```

Example Success Response

```
{
  "success": true,
  "total": 12,
  "limit": 20,
  "offset": 0,
  "include_expired": 0,
  "subscribers": [
    {
      "id": 1,
      "kick_user_id": "123",
      "kick_username": "Viewer",
      "subscription_type": "self",
      "tier": 1
    }
  ]
}
```

Music & Song Request - 3 endpoints

POST

Start / Resume Song

<https://api.missxss.com.tr/v1/start-song>

Resumes a paused song or starts playback.

scope: start-song

limit: 30/min

Parameters

Name	Type	Req	Description
No parameters. Send an empty JSON body or omit body.			

Example Request Body

```
{
}
```

Example Success Response

```
{"success":true}
```

POST

Pause Song

<https://api.missxss.com.tr/v1/stop-song>

Pauses the currently playing song.

scope: stop-song
limit: 30/min

Parameters

Name	Type	Req	Description
No parameters. Send an empty JSON body or omit body.			

Example Request Body

```
{}
```

Example Success Response

```
{"success":true}
```

POST

Skip Song

<https://api.missxss.com.tr/v1/skip-song>

Skips the current song and plays the next one in queue.

scope: skip-song
limit: 30/min

Parameters

Name	Type	Req	Description
No parameters. Send an empty JSON body or omit body.			

Example Request Body

```
{}
```

Example Success Response

```
{"success":true}
```

Points & Economy - 6 endpoints

POST

Add Points

<https://api.missxss.com.tr/v1/add-points>

Adds points to target user. Resolves user by userid (Kick ID) first, then falls back to username.

scope: add-points
limit: 90/min

Parameters

Name	Type	Req	Description
userid	string	no	Target user ID
username	string	no	Target username (without @). Used as fallback if userid is not found.
amount	number	yes	Points amount to add (1 - 99,999,999)
platform	string	yes	Required platform: Kick, Twitch, YouTube or TikTok

Example Request Body

```
{"platform":"kick","userid":"123456","username":"viewer123","amount":100}
```

Example Success Response

```
{"success":true}
```

POST

Remove Points

<https://api.missxss.com.tr/v1/remove-points>

Removes points from target user. Resolves by userid (Kick ID) first, then username fallback.

scope: remove-points
limit: 90/min

Parameters

Name	Type	Req	Description
userid	string	no	Target user ID
username	string	no	Target username (without @). Used as fallback if userid is not found.
amount	number	yes	Points amount to remove (1 - 99,999,999)
platform	string	yes	Required platform: Kick, Twitch, YouTube or TikTok

Example Request Body

```
{"platform":"kick","userid":"123456","username":"viewer123","amount":50}
```

Example Success Response

```
{"success":true}
```

POST

Get User Points

<https://api.missxss.com.tr/v1/get-points>

Returns points/coin/message count for a user. Resolves by userid (Kick ID) first, then username fallback.

scope: get-points
limit: 120/min

Parameters

Name	Type	Req	Description
userid	string	no	Target user ID
username	string	no	Username (without @). Used as fallback if userid is not found.
platform	string	yes	Required platform: Kick, Twitch, YouTube or TikTok

Example Request Body

```
{"platform":"Kick","userid":"123456","username":"viewer123"}
```

Example Success Response

```
{"success":true,"platform":"Kick","user_id":"123","username":"viewer123","displayname":"Viewer123","points":500,"coin":25,"message":100}
```

POST

Get Points Top

<https://api.missxss.com.tr/v1/get-points-top>

Returns points leaderboard (supports limit/offset).

scope: get-points-top
limit: 90/min

Parameters

Name	Type	Req	Description
limit	integer	no	Row count (1-100, default: 20)
offset	integer	no	Start offset (default: 0)
platform	string	yes	Required platform: Kick, Twitch, YouTube or TikTok

Example Request Body

```
{"platform":"Kick","limit":10,"offset":0}
```

Example Success Response

```
{"success":true,"platform":"Kick","limit":10,"offset":0,"total":1200,"users":[{"rank":1,"username":"topuser","points":999999}]}
```

POST

Set Points Directly

<https://api.missxss.com.tr/v1/set-points>

Sets user points to an exact value. Resolves by userid (Kick ID) first, then username fallback.

scope: set-points

limit: 90/min

Parameters

Name	Type	Req	Description
userid	string	no	Target user ID
username	string	no	Username (without @). Used as fallback if userid is not found.
amount	integer	yes	New points value (0 - 99,999,999)
platform	string	yes	Required platform: Kick, Twitch, YouTube or TikTok

Example Request Body

```
{"platform":"kick","userid":"123456","username":"viewer123","amount":2500}
```

Example Success Response

```
{"success":true,"platform":"kick","username":"viewer123","old_points":1200,"points":2500,"changed":1300}
```

POST

Transfer Points

<https://api.missxss.com.tr/v1/transfer-points>

Transfers points from one user to another. For sender/receiver, userid is checked first, then username fallback.

scope: transfer-points

limit: 90/min

Parameters

Name	Type	Req	Description
from_userid	string	no	Sender user ID
from_username	string	no	Sender username (without @), fallback
to_userid	string	no	Receiver user ID
to_username	string	no	Receiver username (without @), fallback
amount	integer	yes	Transfer amount (1 - 99,999,999)
platform	string	yes	Required platform: Kick, Twitch, YouTube or TikTok

Example Request Body

```
{"platform":"kick","from_userid":"111","from_username":"alice","to_userid":"222","to_username":"bob","amount":100}
```

Example Success Response

```
{"success":true,"platform":"kick","from_username":"alice","from_user_id":"111","to_username":"bob","to_user_id":"222","amount":100}
```

Watch Time - 4 endpoints

POST

Adjust Watch Time

scope: adjust-watch-time
limit: 60/min

<https://api.missxss.com.tr/v1/adjust-watch-time>

Adjusts watch time with add/remove/set modes. amount is in minutes. If day is omitted, an old fallback date is used to increase total stats without affecting current day.

Parameters

Name	Type	Req	Description
userid	string	no	Target user ID
username	string	no	Target username (without @). Used as fallback if userid is not found.
mode	string	yes	Operation mode: add remove set
amount	integer	yes	Amount in minutes. min 1 for add/remove, min 0 for set (maximum 99,999,999 minutes)
day	string	no	Target day (YYYY-MM-DD). Fallback date is used when omitted.
platform	string	yes	Required platform: Kick, Twitch, YouTube or TikTok

Example Request Body

```
{ "platform": "Kick", "userid": "123456", "mode": "add", "amount": 30, "day": "2026-04-17" }
```

Example Success Response

```
{ "success": true, "platform": "Kick", "user_id": "123456", "username": "viewer123", "displayname": "Viewer123", "mode": "add", "amount": 30, "amount_e": "e", "day": "2026-04-17", "used_fallback_day": 0, "watch_time": 245, "watch_time_unit": "minute" }
```

POST

Get Watch Time

scope: get-watch-time
limit: 120/min

<https://api.missxss.com.tr/v1/get-watch-time>

Returns watch time and message count for a single user. Use day for one day, date_from/date_to for range, and omit date fields for all-time query.

Parameters

Name	Type	Req	Description
userid	string	no	Target user ID
username	string	no	Target username (without @). Used as fallback if userid is not found.
day	string	no	Single day filter (YYYY-MM-DD)
date_from	string	no	Range start date (YYYY-MM-DD), must be sent with date_to
date_to	string	no	Range end date (YYYY-MM-DD), must be sent with date_from

platform	string	yes	Required platform: Kick, Twitch, YouTube or TikTok
----------	--------	-----	--

Example Request Body

```
{ "platform": "Kick", "userid": "123456", "day": "2026-04-17" }
```

Example Success Response

```
{ "success": true, "platform": "Kick", "user_id": "123456", "username": "viewer123", "displayname": "Viewer123", "query_mode": "day", "day": "2026-04-17", "rom": null, "date_to": null, "watch_time": 245, "watch_time_unit": "minute", "message_count": 18 }
```

POST

Get Watch Time Top

<https://api.missxss.com.tr/v1/get-watch-time-top>

Returns user leaderboard ordered by watch time. Supports filtering by day or date_from/date_to range.

scope: get-watch-time-top
limit: 90/min

Parameters

Name	Type	Req	Description
limit	integer	no	Row count (1-100, default: 20)
offset	integer	no	Start offset (default: 0)
day	string	no	Single day filter (YYYY-MM-DD)
date_from	string	no	Range start date (YYYY-MM-DD), must be sent with date_to
date_to	string	no	Range end date (YYYY-MM-DD), must be sent with date_from
platform	string	yes	Required platform: Kick, Twitch, YouTube or TikTok

Example Request Body

```
{ "platform": "Kick", "day": "2026-04-17", "limit": 10, "offset": 0 }
```

Example Success Response

```
{ "success": true, "platform": "Kick", "query_mode": "day", "day": "2026-04-17", "date_from": null, "date_to": null, "limit": 10, "offset": 0, "total": 1, "watch_time_unit": "minute", "users": [ { "rank": 1, "user_id": "123456", "username": "viewer123", "displayname": "Viewer123", "watch_time": 245, "message_count": 18 } ] }
```

POST

Adjust Watch Time Bulk

<https://api.missxss.com.tr/v1/adjust-watch-time-bulk>

Adjusts watch time for multiple users in one request. amount is in minutes. You can set amount per user row; if omitted, request-level default amount is used.

scope: adjust-watch-time-bulk
limit: 20/min

Parameters

Name	Type	Req	Description
mode	string	yes	Operation mode: add remove set

day	string	no	Target day (YYYY-MM-DD). Fallback date is used when omitted.
amount	integer	no	Default amount in minutes. Used when users[].amount is missing.
users	array	yes	User list of 1-100 items. Each item must include userid or username and optional amount.
platform	string	yes	Required platform: Kick, Twitch, YouTube or TikTok

Example Request Body

```
{ "platform": "Kick", "mode": "add", "day": "2026-04-17", "users": [ { "userid": "123456", "amount": 30 }, { "username": "viewer2", "amount": 15 } ] }
```

Example Success Response

```
{ "success": true, "partial": 0, "platform": "Kick", "mode": "add", "day": "2026-04-17", "used_fallback_day": 0, "amount_unit": "minute", "watch_time": 245, "total_requested": 2, "processed_count": 2, "failed_count": 0, "users": [ { "index": 0, "user_id": "123456", "username": "viewer123", "display_name": "viewer123", "amount": 30 }, { "index": 1, "user_id": "viewer2", "username": "viewer2", "display_name": "viewer2", "amount": 15 } ], "mode": "add", "amount": 30, "day": "2026-04-17", "watch_time": 245, "message_count": 18 }, "failed": [] }
```

Command Management - 8 endpoints

POST

Run Command

<https://api.missxss.com.tr/v1/run-command>

Runs a chat command you defined in the MissXss panel. Can be called by command name or command ID. The command response message is sent and its actions (timeout, ban, voicemod etc.) are automatically processed.

scope: run-command

limit: 90/min

Parameters

Name	Type	Req	Description
command	string	no	Command name (e.g. "!hello" or "hello"). command or id is required.
id	integer	no	Command ID value. command or id is required.
message	string	no	Additional message / arguments to append to the command
username	string	no	Username running the command (default: broadcaster name)

Example Request Body

```
{ "command": "!hello" }
```

Example Success Response

```
{ "success": true, "id": 22029, "command": "!hello", "active": 1, "response": "Hello everyone!" }
```

POST

List Commands (Detailed)

<https://api.missxss.com.tr/v1/list-commands>

Returns all commands for the broadcaster with detailed fields and can be used to discover command IDs for run-command and toggle-command. Response fields: total=total command count; commands[]=command list; id=command ID; command=primary command name; aliases=alternative triggers; active=enabled flag (1/0); show_in_list=show in command list; cooldown_global_seconds=global cooldown; cooldown_user_seconds=user cooldown; message=command response text; permissions=allowed roles/permissions; denied_permissions=blocked roles/permissions; action_json=command action JSON; platform_kick/platform_twitch/platform_tiktok/platform_youtube=platform enable flags; auto_message_interval_minutes=auto-send interval in minutes; auto_message_min_chat_count=minimum chat messages before next auto-send; last_run_at=last run timestamp; last_global_run_at=last global run timestamp; last_user_run_data=per-user last run data; points_cost/coin_cost/delete_cost=command costs; only_game_ids=allowed category/game IDs; blocked_game_ids=blocked category/game IDs; last_auto_message_kick_at/last_auto_message_twitch_at=last auto-send timestamps by platform; raw=raw in-memory command object.

scope: list-commands
limit: 90/min

Parameters

Name	Type	Req	Description
No parameters. Send an empty JSON body or omit body.			

Example Request Body

```
{}
```

Example Success Response

```
{
  "success": true,
  "total": 2,
  "commands": [
    {
      "id": 22029,
      "command": "!hello",
      "aliases": ["!hello", "hello"],
      "active": 1,
      "show_in_list": 0,
      "cooldown_global_seconds": 0,
      "cooldown_user_seconds": 0,
      "message": "Hello!",
      "permissions": "",
      "denied_permissions": "",
      "action_json": "",
      "platform_kick": 1,
      "platform_twitch": 1,
      "platform_tiktok": 1,
      "platform_youtube": 1,
      "auto_message_interval_minutes": 0,
      "auto_message_min_chat_count": 0,
      "last_run_at": 0,
      "last_global_run_at": 0,
      "last_user_run_data": {},
      "points_cost": 0,
      "coin_cost": 0,
      "delete_cost": 0,
      "only_game_ids": [],
      "blocked_game_ids": [],
      "last_auto_message_kick_at": 0,
      "last_auto_message_twitch_at": 0,
      "last_auto_message_tiktok_at": 0,
      "last_auto_message_youtube_at": 0,
      "raw": {}
    }
  ]
}
```

POST

Toggle Command

<https://api.missxss.com.tr/v1/toggle-command>

Enables, disables, or toggles a command by name or ID. mode value: on | off | toggle.

scope: toggle-command
limit: 60/min

Parameters

Name	Type	Req	Description
command	string	no	Command name. command or id is required.
id	integer	no	Command ID value. command or id is required.
mode	string	yes	Mode: on off toggle

Example Request Body

```
{
  "id": 22029,
  "mode": "off"
}
```

Example Success Response

```
{
  "success": true,
  "id": 22029,
  "command": "!hello",
  "active": 0,
  "changed": true,
  "mode": "off"
}
```

POST

Create Command

<https://api.missxss.com.tr/v1/create-command>

Creates a new command and adds it to command list.

scope: create-command
limit: 60/min

Parameters

Name	Type	Req	Description
command	string	yes	Command name (max 50 chars)
message	string	yes	Command response message

Example Request Body

```
{"command":"!hi","message":"Hello everyone!"}
```

Example Success Response

```
{"success":true,"id":22035,"command":"!hi","aliases":["!hi"],"active":1}
```

POST

Update Command

<https://api.missxss.com.tr/v1/update-command>

Updates command message and/or aliases.

scope: update-command
limit: 60/min

Parameters

Name	Type	Req	Description
command	string	no	Command name (command or id required)
id	integer	no	Command ID (command or id required)
message	string	no	New command response
aliases	string array	no	New aliases (comma string or array)

Example Request Body

```
{"id":22035,"message":"Hello there!"}
```

Example Success Response

```
{"success":true,"id":22035,"command":"!hi","aliases":["!hi","!hello"],"message":"Hello there!"}
```

POST

Delete Command

<https://api.missxss.com.tr/v1/delete-command>

Deletes command by name or ID.

scope: delete-command
limit: 60/min

Parameters

Name	Type	Req	Description
command	string	no	Command name (command or id required)
id	integer	no	Command ID (command or id required)

Example Request Body

```
{ "id": 22035 }
```

Example Success Response

```
{ "success": true, "deleted": true, "command": "selam", "id": 22035 }
```

POST

Set Command Cooldown

<https://api.missxss.com.tr/v1/set-command-cooldown>

Sets global and user cooldown values for command.

scope: set-command-cooldown
limit: 60/min

Parameters

Name	Type	Req	Description
command	string	no	Command name (command or id required)
id	integer	no	Command ID (command or id required)
cooldown_global_seconds	integer	no	Global cooldown seconds (0-86400)
cooldown_user_seconds	integer	no	User cooldown seconds (0-86400)

Example Request Body

```
{ "id": 22029, "cooldown_global_seconds": 10, "cooldown_user_seconds": 30 }
```

Example Success Response

```
{ "success": true, "id": 22029, "command": "hello", "cooldown_global_seconds": 10, "cooldown_user_seconds": 30 }
```

POST

Set Command Platforms

<https://api.missxss.com.tr/v1/set-command-platforms>

Updates command platform enable flags.

scope: set-command-platforms

limit: 60/min

Parameters

Name	Type	Req	Description
command	string	no	Command name (command or id required)
id	integer	no	Command ID (command or id required)
platform_kick	boolean integer	no	Kick active flag (1/0)
platform_twitch	boolean integer	no	Twitch active flag (1/0)
platform_tiktok	boolean integer	no	TikTok active flag (1/0)
platform_youtube	boolean integer	no	YouTube active flag (1/0)

Example Request Body

```
{ "id": 22029, "platform_kick": 1, "platform_twitch": 0, "platform_youtube": 1 }
```

Example Success Response

```
{ "success": true, "id": 22029, "command": "hello", "platform_kick": 1, "platform_twitch": 0, "platform_tiktok": 1, "platform_youtube": 1 }
```

AI Bot - 2 endpoints

POST

Update AI Bot Settings

<https://api.missxss.com.tr/v1/ai-bot>

Updates AI Bot settings independently. You can send any single field alone. Supports on/off/toggle for gemini_aktif and ai_sadeceAbone. If ai_text changes, conversation history is automatically cleared.

scope: ai-bot

limit: 20/min

Parameters

Name	Type	Req	Description
gemini_aktif	string	no	AI Bot state: on off toggle
ai_sadeceAbone	string	no	Subscriber-only mode: on off toggle
ai_text	string	no	AI Bot prompt text (max 12000 characters)

Example Request Body

```
{ "gemini_aktif": "on" }
```

Example Success Response

```
{ "success": true, "gemini_aktif": 1, "ai_sadeceAbone": 0, "ai_text_updated": true, "clearai_triggered": false }
```

POST

Clear AI Conversation History

<https://api.missxss.com.tr/v1/clear-ai>

Clears AI conversation history. API equivalent of !clearai command.

scope: clear-ai
limit: 10/min

Parameters

Name	Type	Req	Description
No parameters. Send an empty JSON body or omit body.			

Example Request Body

```
{ }
```

Example Success Response

```
{ "success": true, "cleared": true }
```

Moderation - 12 endpoints

POST

Timeout

<https://api.missxss.com.tr/v1/timeout>

Times out a user for a specified duration. Duration is in minutes (maximum 525600 minutes = 1 year).

scope: timeout
limit: 200/min

Parameters

Name	Type	Req	Description
username	string	yes	Username to timeout
duration	integer	no	Duration (minutes). Min: 1, Max: 525600. Default: 1
reason	string	no	Timeout reason (default: "API Timeout")
platform	string	no	Kick or Twitch (default: Kick)

Example Request Body

```
{ "username": "troll_user", "duration": 5, "reason": "Spamming" }
```

Example Success Response

```
{ "success": true }
```

POST

Ban

<https://api.missxss.com.tr/v1/ban>

Permanently bans a user. Use with caution.

scope: ban
limit: 200/min

Parameters

Name	Type	Req	Description
username	string	yes	Username to ban
userid	string	no	User ID to ban. If sent with username, userid is used preferentially.
reason	string	no	Ban reason (default: "API Ban")
platform	string	no	Kick or Twitch (default: Kick)

Example Request Body

```
{"username":"bad_user","reason":"Rule violation"}
```

Example Success Response

```
{"success":true}
```

POST

Clear Chat

<https://api.missxss.com.tr/v1/clear-chat>

Clears all chat messages.

scope: clear-chat
limit: 15/min

Parameters

Name	Type	Req	Description
No parameters. Send an empty JSON body or omit body.			

Example Request Body

```
{}
```

Example Success Response

```
{"success":true}
```

POST

Manage Shield Mode

<https://api.missxss.com.tr/v1/shield-mode>

Turns shield mode on, off, or toggles it. mode parameter: on, off, toggle.

scope: shield-mode
limit: 15/min

Parameters

Name	Type	Req	Description
------	------	-----	-------------

mode	string	no	Operation mode: on off toggle (default: toggle)
duration	integer	no	Shield-ban lookback window in minutes (min: 0). Used only when enabling/toggle->on.

Example Request Body

```
{"mode": "on"}
```

Example Success Response

```
{"success": true, "shield_mode": 1, "changed": true, "mode": "on"}
```

POST

Get Shield Mode Status

<https://api.missxss.com.tr/v1/get-shield-mode-status>

Returns current shield mode configuration.

scope: get-shield-mode-status
limit: 90/min

Parameters

Name	Type	Req	Description
No parameters. Send an empty JSON body or omit body.			

Example Request Body

```
{}
```

Example Success Response

```
{"success": true, "shield_mode": 1, "shield_ban_enabled": 1, "shield_lookback_minutes": 2}
```

POST

Set Moderation Feature

<https://api.missxss.com.tr/v1/set-moderation-feature>

Enables, disables, or toggles a specific moderation feature.

scope: set-moderation-feature
limit: 10/min

Parameters

Name	Type	Req	Description
feature	string	yes	username_kontrol, spam_korumasi, link_korumasi, kufur_korumasi, caps_korumasi, flood_korumasi, coklu_hesap_spam, ziyaretci_kontrol
mode	string	yes	on off toggle

Example Request Body

```
{"feature": "spam_korumasi", "mode": "on"}
```

Example Success Response

```
{"success": true, "feature": "spam_korumasi", "enabled": 1, "changed": true, "mode": "on"}
```

POST

Get Moderation Status

<https://api.missxss.com.tr/v1/get-moderation-status>

Returns enabled/disabled state for moderation modules. If feature is provided, returns single module status.

scope: get-moderation-status
limit: 90/min

Parameters

Name	Type	Req	Description
feature	string	no	Optional single feature name

Example Request Body

```
{}
```

Example Success Response

```
{
  "success": true,
  "status": {
    "username_kontrol": 1,
    "spam_korumasi": 1,
    "link_korumasi": 1,
    "kufur_korumasi": 1,
    "caps_korumasi": 1,
    "flood_korumasi": 1,
    "esap_spam": 0,
    "ziyaretci_kontrol": 1,
    "kalkan_modu": 0,
    "kalkan_ban": 1,
    "kalkan_sure": 2
  }
}
```

POST

Get Platform Ban List

<https://api.missxss.com.tr/v1/get-platform-ban-list>

Lists ban records from platform_ban_list table.

scope: get-platform-ban-list
limit: 60/min

Parameters

Name	Type	Req	Description
platform	string	no	Kick Twitch YouTube TikTok (optional filter)
limit	integer	no	Row count (1-200, default: 50)
offset	integer	no	Start offset (default: 0)

Example Request Body

```
{
  "platform": "Kick",
  "limit": 20,
  "offset": 0
}
```

Example Success Response

```
{
  "success": true,
  "total": 8,
  "limit": 20,
  "offset": 0,
  "platform": "Kick",
  "bans": [
    {
      "id": 15,
      "platform": "Kick",
      "banned_id": "123",
      "banned_username": "user123",
      "reason": "spam"
    }
  ]
}
```

POST

Get Moderation Log

<https://api.missxss.com.tr/v1/get-moderation-log>

Returns moderation records from event table. Source: event records written by eventlog().

scope: get-moderation-log
limit: 60/min

Parameters

Name	Type	Req	Description
------	------	-----	-------------

type	string	no	Filter: all ban timeout shield (default: all)
limit	integer	no	Row count (1-50, default: 25)
offset	integer	no	Start offset (default: 0)

Example Request Body

```
{"type":"all","limit":25,"offset":0}
```

Example Success Response

```
{"success":true,"source":"event","type":"all","limit":25,"offset":0,"logs":[{"id":991,"type":"Timeout","username":"user1","date":"2023-10-14:20:00"}]}
```

POST

Unban User

<https://api.missxss.com.tr/v1/unban-user>

Removes ban for specified user.

scope: unban-user
limit: 60/min

Parameters

Name	Type	Req	Description
username	string	yes	Username to unban
platform	string	no	Kick or Twitch (default: Kick)

Example Request Body

```
{"username":"old_banned_user"}
```

Example Success Response

```
{"success":true,"username":"old_banned_user","platform":"Kick"}
```

POST

Undo Latest Ban

<https://api.missxss.com.tr/v1/undo-last-ban>

Refreshes the platform live active ban list and removes the latest ban. The ban may have been applied by MissXss, the broadcaster, or any moderator. Kick and Twitch are supported.

scope: undo-last-ban
limit: 30/min

Parameters

Name	Type	Req	Description
platform	string	no	Kick or Twitch (default: Kick)

Example Request Body

```
{"platform":"Kick"}
```

Example Success Response

```
{
  "success": true,
  "action": "unban",
  "platform": "Kick",
  "user": {
    "id": "123",
    "username": "viewer",
    "displayname": "Viewer"
  },
  "original_ban": {
    "rator": "reason": "spam",
    "banned_at": "2026-07-15 18:30:00",
    "method": "Kick API"
  }
}
```

POST

Ban Recent Followers

<https://api.missxss.com.tr/v1/ban-recent-followers>

Quickly ban/timeout the most recent followers. Can ban up to 10 users at once. offset parameter specifies starting position (1 = most recent), count parameter specifies how many users to ban.

scope: ban-recent-followers
limit: 200/min

Parameters

Name	Type	Req	Description
action	string	yes	ban or timeout
offset	integer	no	Starting position (1 = most recent; default: 1)
count	integer	no	How many users to process (1-10; default: 1)
duration	integer	no	Timeout duration in minutes, only for action=timeout (min: 1, max: 525600; default: 1)
reason	string	no	Reason for action (default: "API Ban Recent")
platform	string	no	Kick or Twitch (default: Kick)

Example Request Body

```
{
  "action": "ban",
  "offset": 1,
  "count": 2,
  "reason": "Spam"
}
```

Example Success Response

```
{
  "success": true,
  "action": "ban",
  "processed_count": 2,
  "users": [
    {
      "username": "user1",
      "userid": "123"
    },
    {
      "username": "user2",
      "userid": "456"
    }
  ]
}
```

Discord Core - 4 endpoints

POST

Discord Status

<https://api.missxss.com.tr/v1/discord-status>

Returns Discord bot connection status, guild/channel availability and core permissions.

scope: discord-status
limit: 90/min

Parameters

Name	Type	Req	Description
guild_id	string	no	Discord guild ID (read from active settings if omitted)
channel_id	string	no	Discord message channel ID (optional check)
log_channel_id	string	no	Discord log channel ID (optional check)

```
{"guild_id":"123456789012345678"}
```

```
{
  "success": true,
  "bot_connected": true,
  "guild_found": true,
  "channel_found": true,
  "permissions": {
    "manage_roles": true,
    "move_members": true
  }
}
```

Returns the guilds authorized during Discord connection and their text, announcement and voice channels from the stored channel cache. The response includes every guild and channel ID.

No parameters. Send an empty JSON body or omit body.

 $\{$

```

{"success":true,"total_guilds":1,"total_channels":3,"total_text_channels":2,"total_voice_channels":1,"guilds":[{"id":"12345678901234567890","name":"Server","channels":[{"id":"234567890123456789","name":"general","type":"text"}, {"id":"345678901234567890","name":"announcements","type":"text"}, {"id":"456789012345678901","name":"Lobby","type":"voice"}]}]}

```

Sends text or embed message to your Discord guild channel. Channel ID is required and must belong to your configured guild for security.

embed_color	string	no	Embed color (hex: #FF5733 or decimal: 16721715)
-------------	--------	----	---

```
{"channel_id": "1383215007457611957", "message": "Merhaba Discord!"}
```

Example Success Response

```
{ "success": true, "channel_id": "1383215007457611957", "guild_id": "700705230106394645", "message_id": "1445427371040571642" }
```

POST

List Discord Linked Users

<https://api.missxss.com.tr/v1/discord-linked-users>

Returns paginated Discord-Kick/Twitch linked user records for this broadcaster.

scope: discord-linked-users
limit: 90/min

Parameters

Name	Type	Req	Description
limit	integer	no	Records per page (1-200, default 50)
offset	integer	no	Start offset (default 0)

Example Request Body

```
{ "limit": 50, "offset": 0 }
```

Example Success Response

```
{ "success": true, "total": 120, "limit": 50, "offset": 0, "users": [ { "id": 1, "discord_id": "123", "kick_id": "456", "twitch_id": "789" } ] }
```

Discord Voice Controls - 7 endpoints

POST

List Discord Voice Members

<https://api.missxss.com.tr/v1/discord-voice-members>

Returns all voice channels in a guild or members of a specific voice channel. Guild ID is automatically resolved from account settings.

scope: discord-voice-members
limit: 90/min

Parameters

Name	Type	Req	Description
channel_id	string	no	Voice channel ID to filter a single channel

Example Request Body

```
{ }
```

Example Success Response

```
{ "success": true, "guild_id": "123456789012345678", "total_channels": 2, "channels": [ { "id": "111", "name": "Genel", "member_count": 3 } ] }
```

POST

Discord Voice Kick User

<https://api.missxss.com.tr/v1/discord-voice-kick>

Disconnects the specified user from their current voice channel. Guild ID is automatically resolved from account settings (security).

scope: discord-voice-kick
limit: 30/min

Parameters

Name	Type	Req	Description
discord_id	string	yes	Discord user ID to disconnect

Example Request Body

```
{"discord_id":"55555555555555555555"}
```

Example Success Response

```
{"success":true,"discord_id":"55555555555555555555","kicked":true}
```

POST

Discord Voice Move User

<https://api.missxss.com.tr/v1/discord-voice-move>

Moves the specified user to a target voice channel. When target_channel_id is omitted, the user is pulled into the voice channel currently occupied by the streamer. The request fails if the streamer is not in voice. Guild ID is resolved automatically from account settings.

scope: discord-voice-move
limit: 30/min

Parameters

Name	Type	Req	Description
discord_id	string	yes	Discord user ID to move
target_channel_id	string	no	Optional target voice channel ID. When omitted, the streamer's current channel is used.

Example Request Body

```
{"discord_id":"55555555555555555555"}
```

Example Success Response

```
{"success":true,"discord_id":"55555555555555555555","target_channel_id":"99999999999999999999","moved":true}
```

POST

Discord Voice Mute/Unmute User

<https://api.missxss.com.tr/v1/discord-voice-mute>

Mutes, unmutes, or toggles mute state for the specified user. Guild ID is automatically resolved from account settings (security).

scope: discord-voice-mute
limit: 30/min

Parameters

Name	Type	Req	Description
------	------	-----	-------------

POST

Discord Voice Pull All

<https://api.missxss.com.tr/v1/discord-voice-pull-all>

Pulls users into one room. If from_channel_id is provided, only users in that channel are moved; otherwise users from all voice channels are moved to target_channel_id. Guild ID is automatically resolved from account settings (security).

scope: discord-voice-pull-all
limit: 30/min

Parameters

Name	Type	Req	Description
target_channel_id	string	yes	Target voice channel ID
from_channel_id	string	no	Source voice channel ID (optional)

Example Request Body

```
{"target_channel_id": "999999999999999999"}
```

Example Success Response

```
{"success": true, "target_channel_id": "999999999999999999", "source_channel_id": null, "moved_count": 4}
```

Voicemod - 3 endpoints

POST

Change Voice

<https://api.missxss.com.tr/v1/voicemod-voice-change>

Changes the voice effect via Voicemod. Overlay connection required.

scope: voicemod-voice-change
limit: 60/min

Parameters

Name	Type	Req	Description
voice	string	yes	Voice effect name (e.g. "baby", "deep")
wait_time	integer	no	Effect duration (seconds, default: 60)
original_voice	integer	no	Return to original voice after duration (0 or 1, default: 0)

Example Request Body

```
{"voice": "baby", "wait_time": 60}
```

Example Success Response

```
{"success": true}
```

POST

Play Sound Effect

<https://api.missxss.com.tr/v1/voicemod-effect-play>

Plays a Voicemod meme sound effect (soundboard).

scope: voicemod-effect-play
limit: 60/min

Parameters

Name	Type	Req	Description
voice	string	yes	Effect name

Example Request Body

```
{"voice": "applause"}
```

Example Success Response

```
{"success": true}
```

POST

Hear My Self

<https://api.missxss.com.tr/v1/voicemod-hear-self>

Activates the Voicemod "Hear My Self" feature for a specified duration.

scope: voicemod-hear-self
limit: 60/min

Parameters

Name	Type	Req	Description
wait_time	integer	no	Duration (seconds, default: 60)

Example Request Body

```
{"wait_time": 120}
```

Example Success Response

```
{"success": true}
```